Novokuibyshevsk Petrochemical Company Joint Stock Company Russian Federation, Samara Region, Novokuibyshevsk Email address: nnk@nnk.rosneft.ru tel. (84635) 3-02-20 Quality Management System certificate of compliance with ISO 9001:2015 No. 3110097QM15 specifications. Certificate validity period: through 27.09.2024



EXPORT

QUALITY CERTIFICATE No. 25 Grade A-8 Absorber

TU 38.103349-85 with amendments No 1-14

Date of manufacture	21.12.2021	Product vessel No.	5/1
Date of sampling	21.12.2021	Net weight , kg	57 850
Test date	21.12.2021	Rail tank car No.	5062983

The tests were carried out at the Test Center - Quality Control Department of NNK JSC Certificate of accreditation No. ROSS RU.0001.515720 Date of information entry into the register of accredited entities July 29, 2015.

		5 8		,
Item No.	Indicator	Standard	Actual	Test method
1	Overall view	Dark brown to black	Dark brown to black	TU 38.103349, p.4.2
		viscous liquid	viscous liquid	_
2	Density at 15 °C, g/cm ³	0.7000-0.9500	0.8994	GOST 3900 with
				suppl. as per TU
				38.103349-85,p.4.4
3	Fractional composition			
	a) Initial boiling point, °C	not lower than 25	116	GOST 2177-99 with
	b) final boiling point, °C	not higher than 380	291	amendm.1
	c) amount of fraction boiling out under 185 °C,	no less than 60	58	Method B
	percentage by volume			
4	Copper strip test	withstands the test	withstands the test	GOST 6321-92
5	The content of actual resins, mg/100 cm ³	no more than 15000	5014	GOST 8489-85
6	Volume ratio of water, %	no more than 0,2	absent	GOST 2477-2014
7	Free water content	absent	absent	TU 38.103349, p.4.2

Note: - The test method according to pp. 1 and 7 is not included in the accreditation scope of the Test Center - Quality Control Department of JSC NNK Conclusion: Grade A-8 Absorber meets the technical specifications of:

- TU 38 103349-85 with amendments No. 1-14

upon agreement with the consumer regarding p. 3

The manufacturer guarantees the product quality conformance with this standard, subject to meeting the terms and conditions of transportation and storage. The warranty period of storage is 6 months from the date of manufacture

